

Nitrile Exam Gloves

Features and Benefits

- ▶ Nitrile
- ▶ Thickness (Finger): 3.5mil
- ▶ Powder Free
- ▶ ASTM D6319, D6978
- ▶ Exam Grade
- ▶ Color: Blue
- ▶ Texture: Fingertip
- ▶ Fingertip Thickness: 3.5mil (0.09mm)
- ▶ Length: Standard (240mm)
- ▶ Cuff: Beaded
- ▶ Non-Sterile
- ▶ Chemotherapy Tested

Usage

Dependable for house-wide applications within Healthcare, Labs, EMS and other settings where high-use and disposable exam glove protection is important.



Specifications

Dependable for house-wide applications within Healthcare, Labs, EMS and other settings where high-use and disposable exam glove protection is important.



Ordering Information

ITEM #	SIZE	GLOVES PER BOX	BOXES PER CASE	GLOVES PER CASE
N3200XS	X-Small	200	10	2000
N3200S	Small	200	10	2000
N3200M	Medium	200	10	2000
N3200L	Large	200	10	2000
N3200XL	X-Large	200	10	2000

Spec Information

OVERVIEW	
Material	Nitrile
Powder Content	Powder-Free
Freedom From Holes	1.5 AQL
Surface	Fingertip Textured
Weight (Based on Size M)	3.4 gram
Color	Blue
Cuff Length	240mm, Standard
Not Made With Natural Rubber Latex	Yes
Chemo Rated (Yes/No)	Yes, in accordance with FDA ASTM D6978

THICKNESS MEASUREMENTS	
Finger	.09mm / 3.5mil
Palm	.06mm / 2.5mil

PHYSICAL PROPERTIES		
Criteria	Before Aging	After Aging
Tensile Strength	>/= 14	>/= 14
Elongation	500 (min.)	400 (min.)

DIMENSIONS			
Item#	Size	Palm Width (mm)	Length
N3200XS	Extra-Small	70-80	240mm / 9.5 inches
N3200S	Small	81-90	240mm / 9.5 inches
N3200M	Medium	91-100	240mm / 9.5 inches
N3200L	Large	101-110	240mm / 9.5 inches
N3200XL	Extra-Large	111-120	240mm / 9.5 inches

Nitrile Exam Gloves Powder Free, Beaded Cuff

W-NAVI™, Powder Free Nitrile Examination Glove is a disposable device intended for medical purposes that are worn on the examiner's hand to prevent contamination between the patient and examiner.

PRODUCT CODE: NBR PF USAW35 BB

Features

- ▶ Fingertip textured
- ▶ Powder free
- ▶ Not made with natural rubber latex
- ▶ Beaded Cuff
- ▶ Ambidextrous
- ▶ Blue colour

Specifications

Length (mm)
≥ 230

Thickness Measurements (mm)	
Palm (centre of Palm)	0.07 ± 0.02
Finger (13mm ± 3mm from tip)	0.09 ± 0.02

Physical Properties	Before Aging	After Aging
Tensile Strength (MPa)	≥14	≥500
Elongation (%)	≥14	≥400

Inspection Levels & AQL	Inspection Level	AQL
Watertightness	G1	1.5
Physical Dimensions	S2	4.0
Physical Properties	S2	4.0
Visual Inspection (Major)	G1	2.5
Visual Inspection (Minor)	G1	4.0
Particulate Residue	N = 5	≤ 2mg/glove

Packaging

- 100 gloves per box
- 10 boxes per carton

Regulatory Compliance

- FDA 510(k), MDD 93/42/EEC,

Standards

- ASTM D6319
- ASTM D5151, ASTM D6124,
- EN455 part 1, 2, & 3,

Manufacturing Accreditations

- ISO 9001:2015
- ISO 13485:2016